

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>H04Q 7/38</b>	<b>A1</b>	(11) International Publication Number: <b>WO 00/49826</b> (43) International Publication Date: 24 August 2000 (24.08.00)
(21) International Application Number: PCT/SE00/00240 (22) International Filing Date: 8 February 2000 (08.02.00) (30) Priority Data: 9900563-9 18 February 1999 (18.02.99) SE (71) Applicant: TELEFONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE). (72) Inventor: ERICSSON, Ingela; Knypplerskevägen 36, S-168 38 Bromma (SE). (74) Agents: BERG, S., A. et al.; Albihns Patentbyrå Stockholm AB, P.O. Box 5581, S-114 85 Stockholm (SE).	(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.          Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: METHOD AND APPARATUS IN A TELECOMMUNICATIONS NETWORK COMPRISING LOCALISED SERVICE AREAS, LSA

## (57) Abstract

A method in a cellular telecommunications network in which at least one Localized Service Area, LSA, has been specified, each LSA comprising one or more cells, comprises the following steps: determining if information regarding an LSA has been changed; identifying at least one subscriber belonging to this LSA; transmitting change information to said at least one subscriber belonging to the LSA to update information on a SIM card held by this subscriber. Preferably an indicator is set to indicate if the subscriber belonging to the LSA needs the update information for the type of change made and transmitting update information only if there is such a need. For example, the list of cells belonging to an LSA only needs to be updated if cell information is stored on the SIM card. A node for carrying out the method is also disclosed.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**METHOD AND APPARATUS IN A TELECOMMUNICATIONS NETWORK COMPRISING LOCALISED SERVICE AREAS, LSA****Technical Field**

5 The present invention relates to communication in a cellular network and in particular a cellular network in which Localized Service Areas (LSAs) have been specified.

**Description of Related Art**

10 A cellular network operator can define one or more LSAs in the network, each LSA consisting of one or more cells.

The European Telecommunications Standards Institute (ETSI) is currently developing a new function called Support of LSA (SoLSA), which will enable the use of different tariffs, different access rights or services depending on the geographical  
15 location. The geographical location is based on physical radio resources. Typically, each subscriber will have a home and or office LSA in which the tariff is lower, or certain services are available which are not available to him in other cells.

The information about each subscriber's allowed LSA or LSAs, is stored in the Subscriber Identity Module (SIM) card, and may be updated. When a subscriber is  
20 roaming in the network, an identity signal is received from each cell from which it is currently able to receive signals, and, if one of these signals comes from the allowed LSA, the subscriber camps on this cell. In some cases information about both the allowed LSA and each cell belonging to it is provided. For example, when a cell  
25 belongs to more than one LSA, it may be feasible to transmit only the cell identity instead of all possible LSA identities, which may reduce the paging capacity for the operator.

30 WO 98/30056 discloses a method and means for carrying out the method, by which a subscriber is informed about certain cells in a network. These cells may be defined as preferred cells, e.g. with call charges below the normal tariff. However, the dis-

closed method does not take into consideration possible occurrence of cell identities and LSAs, both stored on a SIM-card. As a consequence of this, each subscriber must be provided with a required list of cell identities, whereby more network capacity is occupied than if only the changes in LSAs are transmitted. Moreover, no check can be made of whether changes have been made in the LSA arrangement, e.g. due to current cell planning.

Each operator can choose if only LSA identity or both cell identity and LSA identity is to be stored on the subscribers' SIM cards. In the case where both cell identity and LSA identity are stored a problem may arise when cells are added to, or removed from an LSA. The information on the SIM card will then be incorrect, and must be updated. Two ways of updating the information have been discussed: The information can be transmitted through the air interface from a Service Management Centre (SMC) in the network using the Short Message Service (SMS) or Unstructured Supplementary Subscriber Data (USSD) service available in the network, or the subscriber's SIM card can be returned to the operator and updated or exchanged.

Updating the SIM card from the SMC requires manual work to identify the SIM cards that are to be updated and to send out the SMS or USSD messages and the manual establishment of a connection to each mobile terminal that is to be updated. Returning the SIM card to the operator by post is time consuming and requires even more manual work. An application of SMS is the SIM data download feature, which is used to update SIM cards.

## **Object of the Invention**

It is an object of the present invention to provide a simplified way of ensuring that each subscriber always has the correct information regarding his/her allowed LSA.

## **Summary of the Invention**

This object is achieved according to the invention by a method in a cellular telecommunications network in which at least one Localized Service Area, LSA, has

been specified, each LSA comprising one or more cells, said method comprising the following steps:

determining if information regarding an LSA has been changed;

identifying at least one subscriber belonging to this LSA;

- 5 transmitting change information to said at least one subscriber belonging to the LSA to update information on a SIM card held by this subscriber.

The object is also achieved according to the invention by a node in a cellular telecommunications network said network comprising at least one Localized Service Area, LSA, has been specified, each LSA comprising one or more cells, said node being characterized in that it comprises

first and second storage means comprising information about the relationship between at least one LSA in the network and the cells belonging to it;

third storage means comprising information about the subscribers belonging to said at least one LSA;

control logic for determining when information regarding an LSA has been changed; function means for effecting the transmission of change information to at least one subscriber in dependence of the contents of said first, second and third storage means.

The method and node according to the invention ensure that the LSA and cell identity information found on each subscriber's SIM card is always correct and updated, with no manual work required.

According to a preferred embodiment the method further comprises the step of determining if the subscriber belonging to the LSA needs the update information for the type of change made and transmitting update information only if there is such a need.

This may be determined by means of an indicator set for each LSA, showing if cell identity information is stored on the SIM card. The node in this case comprises

control logic for determining, on the basis of the indicator, if the change information needs to be transmitted to subscribers in this LSA.

5 This reduces the amount of information that has to be transmitted through the air interface, since in some cases only SIM cards having both cell identity and LSA identity information need to be updated.

Preferably, the node also comprises function means for effecting the transmission of update information to a home location register in the network.

10

In a preferred embodiment said node is a base station controller and the storage means are implemented in or in connection to the base station controller. This is feasible because the base station controller can easily establish connections both to mobile terminals and to the HLR.

15

### **Brief Description of the Drawings**

The apparatus and method according to the invention will be described in more detail in the following, with reference to the appended drawings, in which:

Figure 1 is an overall view of a part of a cellular network;

20 Figure 2 is a block diagram of a cellular network;

Figure 3 is a flow chart of the method according to the invention.

### **Detailed Description of Embodiments**

Figure 1 shows a part of a cellular network comprising a number of hexagonal cells  
25 C1-C9. Three cells, C5, C6 and C8 have been defined as belonging to a LSA, LSA1, the border of which is drawn with a dashed line. The cells C1, C2 and C5 belong to a second LSA, LSA2, the border of which is drawn with a dotted line. Thus, cell C5 belongs both to LSA 1 and to LSA2. Each cell comprises a base station BS1-BS9. Somewhere in the network there is a mobile terminal 1. The mobile terminal 1 will  
30 receive signals from different base stations BS1-BS9 depending on its location. The allowed LSA of the mobile terminal is LSA1, consisting of C5, C6 and C8. The in-

formation about the allowed LSA is stored on the SIM card in the mobile terminal 1, and in the Home Location Register (HLR) in the network, as will be discussed in connection with Figure 2.

5 The base stations transmit signals to identify the LSA and/or cell to which they belong. In the present configuration, Cells C6 and C8 will transmit the information "LSA1", cells C1 and C2 will transmit the information "LSA2" and cell C5 will transmit the information "LSA1" and "LSA2". If a cell belongs to several LSAs, the LSA identity of each LSA must be transmitted. To reduce the amount of information  
10 that has to be transmitted, the base station BS5 can instead transmit only the cell identity, provided the cell identity of each cell in the allowed LSA is also stored on the SIM card. The mobile terminal 1 can then recognize the cell identity "C5" as belonging to its allowed LSA, LSA1.

15 Figure 2 is a block diagram of part of a cellular telecommunications network. Again, a mobile terminal 11 receives signals from one or more base stations 13, of which only one is shown in Figure 2. The base station 13 is connected to a base station controller 15, which controls the function of the base station 13. The base station controller 15 is in turn connected to a cellular exchange (Mobile Services Switching  
20 Centre - MSC) 17 performing the switching functions in the network. Normally, several base stations and base station controllers are connected to one MSC. The MSC 17 is connected to the Home Location Register (HLR) 19, in which general information about each subscriber is stored, including information about the allowed LSA.

25

When the LSA identity or the identities of the cells belonging to the LSA is changed, or an LSA is removed, the information on the SIM card and the HLR entry for each affected subscriber has to be changed. According to the invention this is done from a node in the network, such as the base station controller, from which a  
30 signalling connection to each mobile terminal, and to the HLR, can be established automatically.

To be able to do this the BSC must include, or have access to:

A first database 21 listing the cells in each LSA.

A second database 23 listing the LSAs belonging to each cell.

5 A third database 25 listing the subscribers belonging to each LSA

Control logic 27 to determine when new update information is to be transmitted.

In Figure 2 the databases 21, 23 are shown in a support unit 29 connected to the BSC 15 and the control logic 27 is shown in the BSC 15. Of course each one of the  
10 units 21, 23, 25, 27 could be implemented in the BSC 15 itself, in the support unit 29 or in an existing node in the network, such as the MSC 17.

The node responsible for deciding when to update must also be able to determine when information regarding a particular LSA has been changed. Preferably this is  
15 achieved in that the LSA information is stored in the BSC and updates are made directly in the BSC. In this way, the BSC always has information about which LSAs have been updated and in which way. Alternatively, the information may be stored in any other node in the network and transferred to the BSC when necessary.

20 Although according to a preferred embodiment of the invention the BSC 15 is responsible for deciding when an update is to be made and to initiate the update, the decision to update could be made in another node in the network, such as the MSC 17 which would then instruct the BSC 15 to transmit the update information to the mobile terminals 11. The MSC 17 could then transmit the information directly to  
25 the HLR 19.

As explained above, cell identities are not used in all LSAs. Most changes, for example, a change of cells included in an LSA, will not lead to a need for update in SIM cards that do not have the cell identity information stored on them, since the  
30 LSA identity will still be the same. To reduce the amount of information that has to be transmitted, according to a preferred embodiment of the invention an indicator



may be set for each LSA to indicate if cell identities are stored on the SIM cards or not. If not, the information does not have to be transmitted to the subscribers belonging to this LSA. If the indicator is set for an LSA, that means that the update information has to be transmitted to the subscribers belonging to this LSA.

5

The update information may be transmitted in any way known in the art. Suitable methods are an SMS message to the HLR and a SIM data download message to the SIM card. These methods are well known in the art and will not be discussed in detail here.

10

Figure 3 is a flow chart of the method according to the invention.

Step S1: Information regarding an LSA is changed.

Step S2: Does this information concern all subscribers regardless of whether cell information is stored on the SIM cards or not? If yes, go to step S3; if no, go to step S4.

15

Step S3: Update the information in the HLR regarding the subscribers belonging to this LSA.

Step S4: Is the broadcast indicator set for this LSA? If yes, go to step S5; if no, end of procedure.

20

Step S5: Transmit update information to the subscribers belonging to this LSA. End of procedure.

In step 1, different types of changes may be made. For example, a cell may be split. According to the invention the new cell should inherit the LSA parameters of the old cell. A cell may be removed from the LSA, or a new cell may be added to the LSA. In each of these cases, SIM cards holding information about the cells of the allowed LSA must be updated. Alternatively, general LSA parameters, such as the LSA identity, may be set, which require an update of all SIM cards belonging to the LSA regardless of whether or not they have cell information stored on them.

30

As mentioned above, decision steps S2 and S4 are optional since the broadcast indicator does not have to be used. Without the broadcast indicator update information will always be transmitted to all subscribers belonging to an LSA that has been updated, which will lead to more traffic in the network. If the updates are made at  
5 times when the traffic is low this may not be a big problem.

In steps S3 and S5 the update information may be transmitted in any way known in the art. For example, the SMS or USSD function may be used. A particular application of the SMS function, the SIM data download function, has been developed to  
10 enable information updates on the SIM card.

**Claims**

1. A method in a cellular telecommunications network in which at least one Localized Service Area, LSA, has been specified, each LSA comprising one or more cells,  
5 said method comprising the following steps:  
determining if information regarding an LSA has been changed;  
identifying at least one subscriber belonging to this LSA;  
transmitting change information to said at least one subscriber belonging to the LSA  
to update information on a SIM card held by this subscriber.

10

2. A method according to claim 1 further comprising the step of determining if the subscriber belonging to the LSA needs the update information for the type of change made and transmitting update information only if there is such a need.

15

3. A method according to claim 2, wherein the need is determined by means of an indicator showing if cell identity information is stored on the SIM card.

20

4. A node in a cellular telecommunications network said network comprising at least one Localized Service Area, LSA, has been specified, each LSA comprising one or more cells, characterized in that it comprises

first and second storage means (21, 23) comprising information about the relationship between at least one LSA in the network and the cells belonging to it;  
third storage means (25) comprising information about the subscribers belonging to said at least one LSA;

25

control logic (27) for determining when information regarding an LSA has been changed;

function means (27) for effecting the transmission of change information to at least one subscriber (11) in dependence of the contents of said first (21), second (23) and third (25) storage means.

30

5. A node according to claim 4, further comprising function means (27) for effecting the transmission of update information to a home location register (19) in the network.

5      6. A node according to claim 4 or 5 further comprising control logic for determining (27), on the basis of an indicator set for each LSA, if the change information needs to be transmitted to subscribers in this LSA.

10      7. A node according to any one of the claims 4-6, characterized in that it is a base station controller (15, 29).

15      8. A cellular telecommunications network in which at least one Localized Service Area has been specified, each Localized Service Area comprising one or more cells, characterized in that it comprises at least one node according to any one of the claims 4-7.




Fig. 1




Fig. 2




Fig. 3

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/00240

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: H04Q 7/38

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 9830056 A2 (NOKIA TELECOMMUNICATIONS OY), 9 July 1998 (09.07.98), page 4, line 13 - line 22; page 5, line 14 - page 6, line 27 --	1-8
A	WO 9839940 A2 (TELEFONAKTIEBOLAGET LM ERICSSON (PUBL)), 11 Sept 1998 (11.09.98), page 6, line 19 - page 7, line 4; page 9, line 20 - page 10, line 12 --	1-8
A	WO 9817074 A2 (TELEFONAKTIEBOLAGET LM ERICSSON (PUBL)), 23 April 1998 (23.04.98), page 1, line 30 - page 2, line 3 -----	1-8

☐ Further documents are listed in the continuation of Box C. ☒ See patent family annex.

* Special categories of cited documents:	"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"I" earlier document but published on or after the international filing date	"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search	Date of mailing of the international search report
16 June 2000	22-06-2000
Name and mailing address of the ISA: Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. +46 8 666 02 86	Authorized officer TOMAS LUND/EE Telephone No. +46 8 782 25 00

**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International application No.

PCT/SE 00/00240

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9830056 A2	09/07/98	AU 5324898 A	31/07/98
		FI 2907 U	26/05/97
		FI 970034 A,V	04/07/98
		FI 973615 A	04/07/98
		FI 2859 U	25/04/97
		FI 3106 U	27/10/97
		FI 970035 A,V	04/07/98
WO 9839940 A2	11/09/98	AU 6427698 A	22/09/98
WO 9817074 A2	23/04/98	AU 4730697 A	11/05/98
		DE 19782064 T	30/09/99
		FI 990859 A	16/06/99
		GB 2332830 A	30/06/99
		GB 9908840 D	00/00/00
		US 5930701 A	27/07/99



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINE(S) OR MARK(S) ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**